

2621



Color :  Black-White

UPC Code : 078477807958

Country Of Origin : Mexico

NEMA :  L6-30P

Available Colors :



Black

Locking Plug, 30 Amp, 250 Volt, Industrial Grade, Black & White

30 Amp, 250 Volt, NEMA L6-30P, 2P, 3W, Locking Plug, Industrial Grade, Grounding - Black/White

ROHS Compliant : Yes

Leviton's Black & White line of industrial grade plugs, connectors, flanged inlets, and outlets offer superior performance, long lasting reliability and features that are backed by a limited lifetime warranty:

One piece contacts reduce friction and overheating

Unique cord clamp accepts wide range of cord sizes (.245"-.700")

Rugged nylon construction resists impact, sunlight, chemicals, and rough use

Industry exclusive limited lifetime warranty

Ideal for transfer switches, compressors, and generators

Technical Information

[Electrical Specifications](#)

[Environmental Specifications](#)

Amperage : 30 A

Environment : Dry

Current Interrupting : Certified for current interrupting at full rated current

Flammability : Rated HB or better UL94

Dielectric Voltage : Withstands 2000V per UL498

Operating Temperature : -40° C to 60°C

Grounding : Grounding

Pole : 2

Temperature Rise : Max 30C after 250 cycles OL at 200 percent rated current

Voltage : 250 VAC

Wire : 3

[Material Specifications](#)

[Mechanical Specifications](#)

Assembly Screws : Steel, Zinc Plated

At Rated Voltage : 2 HP

Back Cover : Thermoplastic

Cord Range : 0.520 to 0.930

Blades/Contacts : Solid Brass

Product ID : Ratings are permanently marked on device

Body Material : Impact Modified Nylon


Terminal Accom. : 18-10 AWG

Clamp Insert : Nylon

Terminal ID : Brass-Hot, Green-Ground, Silver-Neutral

Color : Black-White	Torque Range : 10-14 in-lbs
Cord-Clamp : Nylon	Wire Gauge : 16-8 AWG
Terminal Screws : Brass	
Wire Module : Nylon	
Product Features	Standards and Certifications
Brand : Black and White	ANSI : C-73
Color : Black-White	CSA C22.2 No. 42 : File LR-406
Device Type : Locking Plug	NEMA : WD-6
NEMA : L6-30P	NOM : 057
	UL Fed Spec WC-596 : File E13393
	UL498 : File E13393
	Warranty : Limited Lifetime Warranty

Dimensional Drawing



Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·
FAX: +1-800-824-3005

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 ·

Visit our Website at: www.leviton.com

© 2025 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/company/about-leviton/locations

© 2025 Leviton Manufacturing Co., Inc.