



## 2720

30 Amp, 250 Volt, Flush Mount Locking Receptacle, Industrial Grade

30 Amp, 250 Volt 3-Phase, NEMA L15-30R, 3P, 4W, Flush Mtg Locking Receptacle, Industrial Grade, Grounding, V-0-MAX - BLACK

**ROHS Compliant :** Yes

Leviton's Industrial Grade Locking Devices are built to provide unparalleled quality and superior performance in the most severe industrial settings. Leviton combines the best materials available with superior production standards to produce a broad selection of Locking Devices of unmatched flexibility and dependability.

**UPC Code :** 078477809631

**Country Of Origin :** Please Contact Customer Service

**NEMA :**  L15-30R

### Technical Information

#### Electrical Specifications

**Amperage :** 30 A

**Current Limiting :** Full Rated Current

**Dielectric Voltage :**  
Withstands 2000V per UL498

**Grounding :** Grounding

**Phase :** 3-Phase

**Pole :** 3

**Temperature Rise :** Max 30C  
after 250 cycles OL at 200  
percent rated current

**Voltage :** 250 VAC

**Wire :** 4

#### Environmental Specifications

**Environment :** Corrosive

**Flammability :** Rated V-0 per  
UL 94

**Operating Temperature :** -40°  
C to 60°C

#### Material Specifications

**Base Material :** Valox

**Body Material :** Nylon

**Color :** Black

**Cover Material :** Valox 357

**Face Material :** Ultramid

**Grounding Screw :**  
Chromated Brass

**Line Contacts :** Brass .040  
Thick

**Strap Material :** Nickel-Plated  
Brass

**Terminal Clamps :** Nickel-  
Plated Brass

#### Mechanical Specifications

**Cord Range :** 0.595 to 1.150

**Product ID :** Ratings and  
NEMA I.D. permanently marked  
on device

**Screw Terminal Torque :** 14-  
18 in-lbs

**Terminal Accom. :** 14-8 AWG

**Terminal ID :** Marked on Device

**Termination :** Back & Side

**Terminal Screws** : Chromated  
Brass

Product Features

**Base Material** : Valox

**Brand** : V-0-Max

**Color** : Black

**Device Type** : Locking  
Receptacle

**Face Material** : Ultramid

**NEMA** : L15-30R

Standards and Certifications

**ANSI** : C-73

**CSA** : C22.2 No. 42

**NEMA** : WD-6


**NOM** : 057

**UL** : 498

**UL Fed Spec** : W-C-596

**Warranty** : Limited Lifetime  
Warranty Warranty

## Wiring Diagram



**Leviton Manufacturing Co., Inc**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.  
T. Monday-Friday): +1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·  
FAX: +1-800-824-3005 ·

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)  
5386- 1797 ·

**Visit our Website at:** [www.leviton.com](http://www.leviton.com)

© 2025 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without  
notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to:

[www.leviton.com/company/about-leviton/locations](http://www.leviton.com/company/about-leviton/locations)

© 2025 Leviton Manufacturing Co., Inc.