



5262-SW

15 Amp Duplex Receptacle/Outlet, Industrial Grade, Self-Grounding

Duplex Receptacle Outlet, Heavy-Duty Industrial Specification Grade, Smooth Face, 15 Amp, 125 Volt, Back or Side Wire, NEMA 5-15R, 2-Pole, 3-Wire, Self-Grounding - White

ROHS Compliant : Yes

Leviton's line of Heavy-Duty Industrial Grade Receptacles are available with a number of wiring options and features. These heavy-duty receptacles are engineered for fine appearance and top performance in demanding commercial and institutional applications using a durable, thermoplastic face and impact-resistant construction.

Color :  White

UPC Code : 078477141311

Country Of Origin : Mexico

NEMA :  5-15R

Available Colors :



Gray




Brown



Blue



Black



Ivory



Red

Technical Information

AC Horsepower Ratings

Electrical Specifications

At Rated Voltage : 1/2 HP

Amperage : 15 A

Current Limiting : Full Rated Current

Dielectric Voltage : Withstands 2000V per UL498

Grounding : Self-Grounding

Pole : 2

Temperature Rise : Max 30C after 250 cycles OL at 200 percent rated current

Voltage : 125 VAC

Wire : 3

Environmental Specifications

Material Specifications

Flammability : Rated V-2 per UL 94

Body Material : Thermoplastic Nylon

Operating Temperature : -40° C to 60°C

Clamp Nuts : Galvanized Steel

Color : White

Face Material : Thermoplastic Nylon

Ground Clips : Brass

Grounding Screw : Steel 8-32

Line Contacts : Brass Triple-Wipe

Strap Material : Steel

Terminal Screws : Brass 10-32

Mechanical Specifications

Product Features

Product ID : Ratings are permanently marked on device	Body Material : Thermoplastic Nylon
Screw Terminal Torque : 14-18 in-lbs	Color : White
Terminal Accom. : 14-10 AWG	Device Type : Duplex Receptacle Outlet
Terminal ID : Brass-Hot, Green-Ground, Silver-Neutral	Face Material : Thermoplastic Nylon
Termination : Back or Side Wire	Feature 4 : Smooth Face
Torque Range : 14-16 inch pounds	Grade : Heavy-Duty Industrial Specification Grade
	Grounding : Self-Grounding
	NEMA : 5-15R
	Strap Material : Steel

Standards and Certifications

ANSI : C-73

CSA C22.2 No. 42 : File 152105

NEMA : WD-1 & WD-6

NOM : 057

UL Fed Spec WC-596 : File E13399

UL498 : File E13399

Warranty : 2-Year Limited

Patents*

MX321216

US8684771

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S. T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 · FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52) 5386- 1797 ·

Visit our Website at: www.leviton.com

© 2025 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/company/about-leviton/locations

© 2025 Leviton Manufacturing Co., Inc.