



Color :  White

UPC Code : 078477233306

Country Of Origin : Please Contact Customer Service

NEMA :  5-15R

Available Colors :



5325-W

15 Amp Decora Duplex Outlet/Receptacle, Grounding, White

15 Amp, 125 Volt, NEMA 5-15R, 2-Pole, 3-Wire, Decora Duplex Receptacle, Straight Blade, Residential Grade, Grounding, Quickwire Push-In & Side Wired, Steel Strap - White

ROHS Compliant : Yes

- EASY - Quick wire push-in and side wiring for easy installation
- DURABLE - Impact-resistant thermoplastic nylon construction
- CONVENIENT - Shallow depth for maximum wiring room
- COMPATIBLE - For use with Leviton Decora wallplates

Technical Information

Electrical Ratings

Amperage : 15 A

Voltage : 125 VAC

Environmental Specifications

Flammability : Rated V-2 per UL 94

Operating Temperature : -40° C to 60°C

Material Specifications

Body Material : Thermoplastic

Color : White

Face Material : Thermoplastic

Ground Clips : Brass-Plated

Grounding Screw : Steel 8-32

Strap Material : Steel

Terminal Screws : Brass

Mechanical Specifications

Grounding : Grounding

Terminal Accom. : 14-12 AWG

Terminal ID : Brass-Hot, Green-Ground, White-Neutral

Torque Range : 14 – 18 in.-lbs

Product Features

Amperage : 15 A

Body Material : Thermoplastic

Color : White

Face Material : Thermoplastic

NEMA : 5-15R

Pole : 2

Strap Material : Steel

Terminal Accom. : Side wiring accepts #10, #12 and #14 AWG copper (CU) or #10 and #12 copper clad (CC) wire, Quickwire push-in terminals accept #14 AWG solid copper (CU) wire only.

Standards and Certifications

CSA C22.2 No. 42 : File 152105; Class 6233-01

NOM : NOM Certified

NOM Certified : 057

UL 498 : File E13399

UL Listed : File E-13399

Termination : Quickwire Push-In & Side

Type : Duplex Receptacle

Voltage : 125 VAC


Warranty : 2-Year Limited

Wire : 3

Features and Benefits

- Terminal screws accept #10, #12 and #14 AWG copper (CU) or #10 and #12 copper clad (CC) wire
- Quickwire push-in terminals accept #14 AWG solid copper (CU) wire only
- Shallow depth for maximum wiring room
- Double-wipe power contacts for reliable conductivity and plug retention
- Heavy-gauge zinc-plated steel mounting strap
- Additional material added to strap to help reinforce and prevent excessive bending of the break-off tabs
- Limited 2-year warranty

Wiring Diagram



Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·
FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 ·

Visit our Website at: www.leviton.com

© 2025 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/company/about-leviton/locations

© 2025 Leviton Manufacturing Co., Inc.