

7379



50 Amp, 250 Volt, Black & White Locking Flush Mount Receptacle, Industrial Grade

50 Amp, 250 Volt DC/600 Volt AC, Non-NEMA, 3P, 4W, Black & White Locking Flush Mount Receptacle, Industrial Grade, Grounding - BLACK

ROHS Compliant : Yes

- One piece contacts reduce friction and overheating
- Unique cord clamp accepts wide range of cord sizes
- Rugged nylon construction resists impact, sunlight, chemicals, and rough use
- Industry exclusive limited lifetime warranty

UPC Code : 078477804414

Country Of Origin : Mexico

NEMA : Non-NEMA

Technical Information

Electrical Specifications

Amperage : 50 A

Current Interrupting : Certified for current interrupting at full rated current

Current Limiting : Full Rated Current

Dielectric Voltage : Withstands 2000V per UL498

Dielectric Voltage Withstand : 2000V minimum per UL 498

Grounding : Grounding

Maximum Working Voltage : 250V DC/600V AC as rated

Pole : 3

Temperature Rise : Max 30°C temp rise at full-rated current after 150 cycles of OL at 150% rated DC current

Voltage : 250 VAC

Wire : 4

Environmental Specifications

Environment : Dry

Flammability : UL94 V-0

Operating Temperature : -40° C to 75°C

Material Specifications

Assembly Rivets : SS 302/304

Back Cover : Flame-retardant Nylon

Base Material : Nylon

Body and Contract Carrier : Flame-retardant Nylon

Box Terminal : 0.062inch thick Copper

Mechanical Specifications

Product ID : Ratings and Catalogue No. molded into face

Terminal Accom. : AWG #10 to #6 for Ground (stranded only), and AWG #10 to #4 for line terminals

Terminal ID : X, W, Y, and Green for ground

Clamp Nuts : Brass

Color : Black

Compression Nut, Strain Relief : 0.100-inch thick Brass

Connector Contact - Binding Plate : 0.100-inch thick Brass

Connector Contact - Spring : 0.041-inch thick Brass

Contact Rivet : Brass

Face Material : Nylon

Face Module : Flame-retardant Nylon

Grounding Screw : Brass

Line Contacts : Brass

Mounting Screws : SS 302/304

Mounting Strap : Single piece SS 302/304

Shroud : .062-inch thick Nickel Plated Steel

Terminal Block : 0.062-inch thick Copper


Terminal Screws : Brass

Terminal Set Screw : SS 302 /304

Yoke : Brass

<u>Product Features</u>	<u>Standards and Certifications</u>
Base Material : Nylon	ANSI : C-73
Brand : Black and White	CSA C22.2 No. 42 : File 152105
Color : Black	NEMA : WD-6
Device Type : Locking Receptacle	NOM : 057
Face Material : Nylon	RoHS : Compliant
NEMA : Non-NEMA	UL 498 : File E13399
Standards and Certifications : UL	UL Fed Spec WC-596 : File E13399
Strap Material : Brass	UL498 : File E13399
Termination : Back & Side	Warranty : Limited Lifetime Warranty
Warranty : Limited Lifetime Warranty	

Dimensional Drawing



Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·
FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 ·

Visit our Website at: www.leviton.com

© 2025 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/company/about-leviton/locations

© 2025 Leviton Manufacturing Co., Inc.