

# 7411-C



**UPC Code :** 078477829691

**Country Of Origin :** Mexico

Locking Plug, 20 Amp, 120/208 Volt, Industrial Grade, Black & White

20 Amp, 120/208 Volt 3-Phase Y, Non-NEMA, 4P, 4W, Locking Plug, Industrial Grade, Non-Grounding - BLACK-WHITE

Leviton's Black & White line of industrial grade plugs, connectors, flanged inlets, and outlets offer superior performance, long lasting reliability and features that are backed by a limited lifetime warranty:

- One piece contacts reduce friction and overheating
- Unique cord clamp accepts wide range of cord sizes
- Rugged nylon construction resists impact, sunlight, chemicals, and rough use
- Industry exclusive limited lifetime warranty

## Technical Information

| <u>Environmental Specifications</u>  | <u>Material Specifications</u>               |
|--|--|
| <b>Environment :</b> Dry   | <b>Assembly Screws :</b> Steel, Zinc Plated  |
| <b>Flammability :</b> Rated HB or better UL94  | <b>Back Cover :</b> Thermoplastic            |
| <b>Operating Temperature :</b> -40° C to 60°C  | <b>Blades/Contacts :</b> Solid Brass         |
|  | <b>Body Material :</b> Impact Modified Nylon |
|  | <b>Clamp Insert :</b> Nylon                  |
|  | <b>Color :</b> Black-White                   |
|  | <b>Cord-Clamp :</b> Nylon                    |
|  | <b>Terminal Screws :</b> Brass               |
|  | <b>Wire Module :</b> Nylon                   |
| <u>Mechanical Specifications</u>   | <u>Product Features</u>                      |
| <b>Amperage :</b> 20 A   | <b>Brand :</b> Black and White               |
| <b>Cord Range :</b> .595 - .895  | <b>Color :</b> Black-White                   |
| <b>Current Interrupting :</b> Certified for current interrupting at full rated current |  |
| <b>Dielectric Voltage :</b><br>Withstands 2000V per UL498                              |  |
| <b>Grounding :</b> Non-Grounding   |  |
| <b>Phase :</b> 3-Phase WYE   |  |
| <b>Pole :</b> 4  |  |
| <b>Product ID :</b> Ratings and NEMA I.D. permanently marked on device                 |  |

**Temperature Rise :** Max 30C  
at 250 cycles OL at 200 pct  
rated current

**Terminal Accom.** : 18-10 AWG

**Terminal ID :** Brass-Hot,  
Green-Ground, Silver-Neutral

**Torque Range :** 10-14 in-lbs

**Voltage :** 120/208 VAC

**Wire :** 4

**Wire Gauge :** 14-10 AWG

Standards and Certifications

**ANSI :** C-73

**CSA C22.2 No. 42 :** File LR-406

**NEMA :** WD-6

**NOM :** 057

**UL498 :** File E13393

**Warranty :** Limited Lifetime  
Warranty Warranty

**Patents\***

US12149019

US10431922

US11515665

MX417278

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

**Leviton Manufacturing Co., Inc**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·  
FAX: +1-800-824-3005 ·

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)  
5386- 1797 ·

**Visit our Website at: [www.leviton.com](http://www.leviton.com)**

© 2025 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to:  
[www.leviton.com/company/about-leviton/locations](http://www.leviton.com/company/about-leviton/locations)

**© 2025 Leviton Manufacturing Co., Inc.**