



Color : (

**UPC Code:** 078477815205

Country Of Origin: United States

White

NEMA : (

) 5-15R

### **Available Colors:**





Ivory







Grav

Light Almond

# **CR15-W**

15 Amp Duplex Receptacle/Outlet, Commercial Grade, Self-Grounding

Duplex Receptacle Outlet, Commercial Specification Grade, Indented Face, 15 Amp, 125 Volt, Side Wire, NEMA 5-15R, 2-Pole, 3-Wire, Self-Grounding - White

**ROHS Compliant:** Yes

Leviton's line of Heavy-Duty Specification Grade receptacles are designed and manufactured to withstand the most demanding environments. Available in a wide variety of configurations, including isolated ground, tamper-resistant, etc., these Commercial Grade devices are the electrical contractor's choice for use in hotels, schools, hospitals and commercial office buildings.

#### **Technical Information**

**AC Horsepower Ratings** 

At Rated Voltage: 1/2 HP

**Electrical Specifications** 

Amperage: 15 A

Current Limiting: Full Rated

Current

**Dielectric Voltage:** 

Withstands 2000V per UL498

Grounding: Self-Grounding

**Pole**: 2

Temperature Rise: Max 30C after 100 cycles OL at 150 percent rated current

Voltage: 125 VAC

Wire: 3

**Environmental Specifications** 

Operating Temperature :  $-40^{\circ}$ 

C to 60°C

Material Specifications

**Body Material**: Nylon

Color : White

Face Material: Nylon

**Ground Clips**: Brass-Plated **Grounding Screw**: Steel 8-32

Line Contacts : Brass Double

Wipe .031 Thick

Strap Material: Zinc-Plated

Steel

Terminal Screws : Steel 8-32

Mechanical Specifications Product Features

Body Material: Nylon

**Product ID**: Ratings are permanently marked on device

**Screw Terminal Torque**: 14-

18 in-lbs

Terminal Accom.: 14-10 AWG

**Terminal ID**: Brass-Hot, Green-Ground, Silver-Neutral

Termination: Side Wire

Color: White

**Device Type :** Duplex Receptacle Outlet

Face Material: Nylon

Feature: Indented Face

**Grade :** Commercial Specification Grade

**Grounding:** Self-Grounding

**NEMA:** 5-15R

## Standards and Certifications

**ANSI:** C-73

CSA C22.2 No. 42: File

152105

**NEMA:** WD-1 & WD-6

**NOM:** 057

**UL498**: File E13399

Warranty: 10-Year Limited

### Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

### Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 · FAX: +1-800-824-3005 ·

### Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52) 5386- 1797 ·

### Visit our Website at: www.leviton.com

© 2025 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

## Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/company/about-leviton/locations

## © 2025 Leviton Manufacturing Co., Inc.