

16252-W



Color :  White

UPC Code : 078477819685

Country Of Origin : Mexico

NEMA :  5-15R

Available Colors :



Brown



Ivory



Black



Light Almond



Gray

15 Amp Decora Plus Duplex Receptacle/Outlet, Industrial Grade, Self-Grounding

Decora Plus Duplex Receptacle Outlet, Heavy-Duty Industrial Specification Grade, Smooth Face, 15 Amp, 125 Volt, Back and Side Wire, NEMA 5-15R, 2-Pole, 3-Wire, Self-Grounding - White

ROHS Compliant : Yes

Leviton's line of Heavy-Duty Specification Grade receptacles are designed and manufactured to withstand the most demanding environments. Available in a wide variety of configurations, including isolated ground, tamper-resistant, etc., these Commercial Grade devices are the electrical contractor's choice for use in hotels, schools, hospitals and commercial office buildings.

Technical Information

AC Horsepower Ratings

Amperage : 15 A

At Rated Voltage : 1/2 HP

Current Limiting : Full Rated Current

Dielectric Voltage :
Withstands 3000V min

Grounding : Self-Grounding

Pole : 2

Temperature Rise : Max 30°C temperature rise at full rated current

Voltage : 125 VAC

Wire : 3

Electrical Specifications

Amperage : 15 A

Current Limiting : Full Rated Current

Dielectric Voltage :
Withstands 3000V min

Flammability : Rated V-2 per UL 94

Grounding : Self-Grounding

Operating Temperature : -40° C to 60°C

Pole : 2

Temperature Rise : Max 30°C temperature rise at full rated current

Voltage : 125 VAC

Wire : 3

Environmental Specifications

Body Material : PBT Polyester Blend

Color : White

Face Material : PBT Polyester Blend

Flammability : Rated V-2 per UL 94

Ground Clips : Brass-Plated

Material Specifications

Body Material : PBT Polyester Blend

Color : White

Face Material : PBT Polyester Blend

Ground Clips : Brass-Plated

Grounding Screw : #8 Hex Head, Triple-Drive Brass

Grounding Screw : #8 Hex Head, Triple-Drive Brass	Line Contacts : 0.030" Phosphor Bronze
Line Contacts : 0.030" Phosphor Bronze	Product ID : Ratings are permanently marked on device
Operating Temperature : -40° C to 60°C	Strap Material : Steel (Galvanized G60)
Strap Material : Steel (Galvanized G60)	Terminal Accom. : 14-10 AWG
Terminal Screws : #8 Triple-Drive Brass	Terminal ID : Brass-Hot, Green-Ground, Silver-Neutral
	Terminal Screws : #8 Triple-Drive Brass
	Termination : Back and Side Wire

Mechanical Specifications

Brand : Decora Plus	Product Features
Color : White	Brand : Decora Plus
Device Type : Duplex Receptacle Outlet	Device Type : Duplex Receptacle Outlet
Grade : Heavy-Duty Industrial Specification Grade	Grade : Heavy-Duty Industrial Specification Grade
NEMA : 5-15R	NEMA : 5-15R

Product ID : Ratings are permanently marked on device

Screw Terminal Torque : 14-18 in-lbs

Terminal Accom. : 14-10 AWG

Terminal ID : Brass-Hot, Green-Ground, Silver-Neutral

Termination : Back and Side Wire

Standards and Certifications

ANSI : C-73

Applicable Standards : UL 498, Fed Spec W-C-596, CSA C22.2 No.42

At Rated Voltage : 1/2 HP

Certification/Listing : cULus, NON-ANCE

RoHS : RoHS Compliant

Warranty : 10-Year Limited

Patents^{*}

MX321216

US8684771

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 · FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52) 5386- 1797 ·

Visit our Website at: www.leviton.com

© 2025 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/company/about-leviton/locations

© 2025 Leviton Manufacturing Co., Inc.