

515CR



UPC Code : 078477841549

Country Of Origin : Mexico

NEMA :  5-15R

15 Amp, 125 Volt, NEMA 5-15R, 2Pole, 3Wire, Connector, Straight Blade, Rubber, Black

15 Amp, 125 Volt, NEMA 5-15R, 2Pole, 3Wire, Connector, Straight Blade, Rubber - Black

ROHS Compliant : Yes

Leviton offers a large selection of 15, 20, 30 and 50 Amp Commercial Grade Straight Blade Plugs and Connectors, available in a wide variety of features. These rugged performers are moisture, chemical and abuse-resistant, And they're ideal for indoor and outdoor use. Our EPTR rubber-backed plugs and connectors stand up to rough use, protecting against dirt and moisture. The deep-slotted, backed-out terminal screws draw backwire clamps securely over stripped leads for maximum conductivity.

Technical Information

Electrical Specifications Environmental Specifications

Amperage : 15 A

Flammability : Rated V-2 per

UL 94

Current Interrupting : Certified for current interrupting at full rated current

Operating Temperature : -40° C to 60°C

Dielectric Voltage :

Withstands 2000V per UL498

Grounding : Grounding

Pole : 2

Temperature Rise : Max 30C after 50 cycles OL at 150 percent rated current

Voltage : 125 VAC

Wire : 3

Material Specifications

Mechanical Specifications

Assembly Screws : Steel, Zinc Plated

Cord Range : .245 - .700

Blades/Contacts : Brass

Product ID : Ratings and NEMA I.D. permanently marked on device

Body Material : EPTR Rubber

Terminal Accom. : 18-12 AWG

Color : Black

Terminal ID : Brass-Hot, Green-Ground, Silver-Neutral

Product Features

Standards and Certifications

Color : Black

ANSI : C-73

Grade : Residential

CSA C22.2 No. 42 : File LR-406

NEMA : 5-15R

NEMA : WD-6

Series : 515PV

NOM : 057

Standards and Certifications


UL498 : File E13393

: UL/CSA

Wavelength Selection

Wire Gauge : 18-12 AWG

Wiring Diagram



5-15R

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 · FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52) 5386-1797 ·

Visit our Website at: www.leviton.com

© 2025 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/company/about-leviton/locations

© 2025 Leviton Manufacturing Co., Inc.