



515PR

15 Amp, 125 Volt, NEMA 5-15P, 2-Pole, 3-Wire Plug, Straight Blade, Rubber, Black

15 Amp, 125 Volt, NEMA 5-15P, 2-Pole, 3-Wire Plug, Straight Blade, Rubber - Black

ROHS Compliant : Yes

Technical Information

Electrical Specifications

Amperage : 15 A

Current Interrupting : Certified for current interrupting at full rated current

Dielectric Voltage : Withstands 2000V per UL498

Grounding : Grounding

Pole : 2

Temperature Rise : Max 30C after 50 cycles OL at 150 percent rated current

Voltage : 125 VAC

Wire : 3

Environmental Specifications

Flammability : Rated V-2 per UL 94

Operating Temperature : -40° C to 60°C

UPC Code : 078477841426

Country Of Origin : Mexico

NEMA :  5-15P

Material Specifications

Assembly Screws : Steel, Zinc Plated

Blades/Contacts : Brass

Body Material : EPTR Rubber

Color : Black

Mechanical Specifications

Cord Range : 0.245 to 0.700

Product ID : Ratings and NEMA I.D. permanently marked on device

Terminal Accom. : 18-12 AWG

Terminal ID : Brass-Hot, Green-Ground, Silver-Neutral

Product Features

Color : Black

Grade : Residential

NEMA : 5-15P

Series : 515PV

Standards and Certifications : UL/CSA

Wire Gauge : 18-12 AWG

Standards and Certifications

ANSI : C-73

CSA C22.2 No. 42 : File LR-406

NEMA : WD-6

NOM : 057

UL498 : File E13393

Warranty : 2-Year Limited

Wiring Diagram

