

99W75-S



UPC Code : 078477519769

Country Of Origin : Mexico

NEMA :  L15-30R

Wetguard Watertight Locking Outlet

30 Amp, 250 Volt 3-phase, NEMA L15-30, 3P, 4W, Locking Single Outlet, Industrial Grade, Grounding, Wetguard - YELLOW

ROHS Compliant : Yes

- BATTLE THE ELEMENTS- Resistant to water, acids, alkalies, and many automotive and industrial lubricants and solvents.
- ADVANCED LID DESIGN- Our spring-loaded flip lid is impact and chemical resistant with a Valox® PBT cover
- MORE SECURE- Dual-hasp provides additional lockout /tagout option for added security.
- DURABLE- Ideal for harsh environments with added resistance against heat, chemical corrosion, and physical abrasion

Technical Information

Electrical Specifications

Amperage : 30 A

Current Limiting : Full Rated Current

Dielectric Voltage : Withstands 2000V per UL498

Grounding : Grounding

Phase : 3-Phase

Pole : 3

Temperature Rise : Max 30C after 250 cycles OL at 200 percent rated current

Voltage : 250 VAC

Wire : 4

Environmental Specifications

Enclosure Rating : NEMA 4, 4X, 12 IEC IP66

Environment : Wet

Flammability : Rated V-2 per UL 94 (wiring module)

Operating Temperature : -40° C to 60°C

Material Specifications

Blades/Contacts, Terminal Clamps : Electroless Nickel-coated Brass

Cover Gasket : Santoprene TPV

Cover/Lid : Valox PBT

Mounting and Assembly

Screws : Stainless steel, non-magnetic

Terminal Screws : Electroless Nickel-coated Brass

Mechanical Specifications

Product ID : Ratings and NEMA I.D. permanently marked on device

Screw Terminal Torque : 12-14 in-lbs

Terminal Accom. : #12 AWG to #8 AWG

Terminal ID : Brass-Hot, Green-Ground, Silver-Neutral

Torque Range : 10-12 in-lbs

Torsion Spring Mechanism :

Stainless Steel

Wiring Module : Nylon

Wiring Module Mounting Cup

: Valox PBT

Product Features

Brand : Wetguard

Color : Yellow

Device Type : Locking Outlet

NEMA : L15-30R

Standards and Certifications

ANSI : C-73

CSA : C22.2 No. 42

NEMA : WD-6

NOM : 057

UL : 498

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·
FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 ·

Visit our Website at: www.leviton.com

© 2025 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/company/about-leviton/locations

© 2025 Leviton Manufacturing Co., Inc.