

ARTICLE 725

CCTV COAXIAL CABLE

**APPLICATIONS:**

AUDIO/VIDEO, RADIO FREQUENCY, CCTV TRANSMISSIONS, SUNLIGHT RESISTANT

CODE RESTRICTIONS:

FOR USE WITH GENERAL PURPOSE EXCEPT IN RISERS AND PLENUMS

FEATURES:

AVAILABLE IN 500 FT. OR 1000 FT. BOXES OR SPOOLS, ALSO AVAILABLE IN BULK. SEQUENTIAL FOOTAGE MARKINGS

CONSTRUCTION:

FOAMED DIELECTRIC CORE OVER SOLID COPPER CENTER CONDUCTOR, BARE COPPER BRAID SHIELD, JACKET COLORS: BLACK, WHITE

CCTV Coaxial Cable

STYLE	SHIELD	AWG	NOM. VP	NOM. O.D.	NOM. IMP	UL LISTINGS	AVG. LBS. PER MFT	SPEC #
RG59/U	95% BC	20 BC	78	.240	75 OHMS	CM/CL2	35	C30022
RG6/U	95% BC	18 BC	78	.270	75 OHMS	CM/CL2	44	C40009
RG11/U	95% BC	14 BC	78	.400	75 OHMS	CL3	87	C60003
RG59/U + 18/2 Siamese	95% BC	20 BC + 18 BC	78	.360 X .285	75 OHMS	CM/CL3	60	H90369
RG6/U + 18/2 Siamese	95% BC	18 BC + 18 BC	78	.275 X .445	75 OHMS	CM/CL2	64	H90767
RG6/U + 16/2 Siamese	95% bc	18 BC + 18 BC	78	.279 X .475	75 OHMS	CM.CL2	72	H90454

CCTV COAXIAL CABLE, PLENUM RATED

**APPLICATIONS:**

AUDIO/VIDEO, RADIO FREQUENCY, CCTV TRANSMISSIONS

CODE RESTRICTIONS:

FOR USE WITH GENERAL PURPOSE

FEATURES:

AVAILABLE IN 500 FT. OR 1000 FT. BOXES OR SPOOLS, SEQUENTIAL FOOTAGE MARKINGS

CONSTRUCTION:

FOAMED DIELECTRIC CORE OVER SOLID BARE COPPER CENTER CONDUCTOR, BARE COPPER BRAID SHIELD, JACKET COLOR: OFF-WHITE

CCTV Coaxial Cable, Plenum Rated

STYLE	SHIELD	AWG	NOM. VP	NOM. O.D.	NOM. IMP	UL LISTINGS	AVG. LBS. PER MFT	SPEC #
RG59/U	95% BC	20 BC	82	.193	75 OHMS	CMP/CL2P	28	D30009
RG6/U	95% BC	18 BC	82	.221	75 OHMS	CMP/CL2P	37	D40012
RG11/U	95% BC	14 BC	82	.335	75 OHMS	CL3P	91	D60001
RG59/U + 18/2 Siamese	95% BC	20 BC + 18 BC	82	.421 X .245	75 OHMS	CMP/CL3P	42	H90224
RG6/U + 18/2 Siamese	95% BC	18 BC + 18 BC	82	.232 X .420	75 OHMS	CMP/CL2P	55	H90794
RG6/U + 16/2 Siamese	95% BC	18 BC + 16 BC	82	.275 X .490	75 OHMS	CMP/CL2P	62	H90061