



Color :  Red

UPC Code : 078477725016

Country Of Origin : China

NEMA :  5-15R

Available Colors :



GFNT1-HGR

15 Amp SmartlockPro® GFCI Receptacle/Outlet, Hospital Grade

SmartlockPro Self-Test GFCI Duplex Receptacle Outlet, Extra Heavy-Duty Hospital Grade, Wallplate Included, Power Indication, 15 Amp, 20 Amp Feed-Through, 125 Volt, Back or Side Wire, NEMA 5-15R, 2-Pole, 3-Wire, Self-Grounding - Red

Technical Information

AC Horsepower Ratings

At Rated Voltage : 1 HP

Electrical Specifications

Amperage : 15 A & 20 A Feed-Through

Grounding : Self-Grounding

Pole : 2

Short Circuit Current Rating : 10kA

Voltage : 125 VAC

Wire : 3

Environmental Specifications

Flammability : Rated V-0 per UL 94

Operating Temperature : -35C to +66C

Material Specifications

Body Material : Polycarbonate

Face Material : PBT

Ground Clips : Brass

Grounding Screw : Plated Steel

Line Contacts : Brass

Strap Material : Galvanized Steel

Terminal Clamp : Brass

Terminal Screws : Plated Steel

Mechanical Specifications

Product ID : Ratings are permanently marked on device

Screw Terminal Torque : 14-18 in-lbs

Terminal Accom. : 14-10 AWG solid or stranded

Terminal ID : Brass-Hot, Green-Ground, Silver-Neutral

Termination : Back or Side Wire

Trip Level : Class A, 5mA plus or minus 1mA

Product Features

Brand : SmartlockPro

Color : Red

Device Type : Duplex Receptacle Outlet

Feature : Wallplate Included|Power Indication|Self-Test

Function : GFCI

Grade : Extra Heavy-Duty Hospital Grade

NEMA : 5-15R

Standards and Certifications

Warranty

ANSI : C-73

Warranty : 2-Year Limited

Applicable Standards : UL
943, UL 498, CSA C22.2 No.
42 & 144, FedSpec W-C-596

Certification/Listing : UL,
CSA, NOM-ANCE

NEMA : WD-1 & WD-6

Patents*

CA2730014	CA2865659
MX302458	MX302458
MX302458	MX308495
MX308495	MX308495
MX344697	US10483066
US11456138	US7697252
US7697252	US7697252
US8587914	US8587914
US8587914	US8599522
US8599522	US8599522
US8944859	US9053886
US9053886	US9053886
US9077091	US9276393

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·
FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 ·

Visit our Website at: www.leviton.com

© 2025 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/company/about-leviton/locations

© 2025 Leviton Manufacturing Co., Inc.