


Passive Ceiling Zone Enclosure

The Passive Ceiling Zone Enclosure is a flexible, economic solution to support zone cabling in a variety of enterprise workspaces, enabling shorter easy-to-manage connections directly to building devices such as LED lights, security cameras, wireless access points or building automation controllers, or to outlets serving voice, data or other systems. Designed to meet UL 2043 plenum requirements and install flush within a 2 X 2 ft. drop ceiling tile space, this lightweight EIA/ECA-310-E compliant ceiling enclosure is low profile while offering a 4U adjustable rack system with a recommended maximum 96-port count for copper cabling.



Aesthetically Pleasing
Installs flush within drop ceiling and cut ceiling panels easily slide into the door to blend into decor.



Adjustable
Fully adjustable 4U rack system supports a load capacity of 31.7 kg (70 lbs.) with less depth than other ceiling enclosures.



Accessibility Hinged door and tilting bracket enable easy access to ports to facilitate terminations in a cost-effective zone cabling topology.


Product Information

Ordering Information

Part Number	Description
ZU-C4P-L02	Passive Ceiling Zone Enclosure, 4U, White, Key lock. Includes 8 plastic bushings
ZU-C4P-T02	Passive Ceiling Zone Enclosure, 4U, White, thumb lock. Includes 8 plastic bushings
ZU-CN2-M	Optional 2-inch metal chase nipple. Sold in increments of 1

SPECIFICATIONS

Weight	8 kg (18 lbs.)
Load Rating	Static: 31.7kg (70 lbs.)
Color	White
Cable Access Openings	16 (8 per side) 50mm (2 in.)
Material	15 AWG Aluminum (Door is 16 AWG)
Material Compliance	RoHS, Lead-free, Halogen free, PVC-free
Finish	Textured Powder Coat
Standards Compliance	EIA/ECA-310-E UL 1863 Meets UL 2043 Plenum Requirements



Zone Cabling ROI

While dependent upon the exact number of moves, adds, and changes (MACs) performed per year, typical zone cabling plants of any size planned with 25% spare port availability not only significantly reduce client disruption, but allow the building owner to recoup the cost of the extra port capacity within a two to five year span or after reaching the ROI threshold (i.e. either 14 moves and 17 adds or 16 moves and 20 adds depending upon cabling type). For more information please visit www.siemon.com.

Because we continuously improve our products, Siemon reserves the right to change specifications and availability without prior notice.

North America P: (1) 860 945 4200	Mexico P: (521) 556 387 7708/09/10	Latin America P: (571) 657 1950/51/52	Europe P: (44) 0 1932 571771	China P: (86) 215385 0303	India, Middle East & Africa P: (971) 4 3689743
Asia Pacific P: (61) 2 8977 7500	Siemon OEM Technologies P: (1) 860 945 4213 www.siemon.com/OEM				

